

---

## **Polished Plaster Banding Specification Details.**

### **Description**

This is a lime based polished plaster finish that requires special skills and experienced applicators to achieve good high quality end results. Applications and products are provided directly from Walleffects Ltd. This finish is normally a contrast between a polished surface and a textured surface.

### **Site Name**

*[Add you site location here]*

### **Areas to receive specialist finishes**

*[Add description here of all areas to be finished]*

### **Drawings**

*[Add drawing reference number etc]*

### **Substrate**

*[Add your preferred substrate here with a reference to the relevant data sheet.]*

Render, drylined surfaces, plaster board are all suitable please check the substrate documents for more advice. Substrates all need to be fully dry, free from dust, dirt, moisture, straight, plumb and with no bumps or ridges.

Please check our **plaster substrate documents** for more details or email our technical adviser [tech@walleffects.co.uk](mailto:tech@walleffects.co.uk).

### **Finish**

*[Add you finish here]*

### *Options.*

Polished surface on top of a textured surface or as per sample.

---

### **Texture required for banding**

Surface 1 polished.

[Add your polished surface here, ie Classic or Carrara Marmorino as per your sample.]

Surface 2 textured.

[Add your textured surface here, ie Intonachino [select grain size] or Chamois as per your sample.]

### **Banding Size**

[Add polished band width here]

[Add textured band width here]

### **Band direction**

[Add vertical or horizontal here]

[Add any custom banding requests, ie non straight lines. Please send Walleffects a sketch prior to specification to ensure this can be achieved. Please include band details in drawings]

### **Colour**

Colour no [add number here for both textures]

Sample reference [add numbers here]

Custom colours [add a reference here, ie RAL or paint number]

*Polished Plaster finishes are not a uniform colour and will have natural shade variations.*

*Small samples may not show this.*

### **Thickness**

0.5mm to 1mm on skim coated substrates not using our anti crack system.

2mm to 3mm using our anti crack system. [Highly recommended]

Polished bands will be raised between 0.5 and 1mm above the textured coat.

### **Programme**

Application times will vary depending on the specific project. Finishes need to be applied late in the construction normally when decorating is taking place. Applications are normally booked 8 weeks in advance. Banding done in polished plasters has a minimum 3 days application time due to the various required layers. Please contact Walleffects for specific application times:

[tech@walleffects.co.uk](mailto:tech@walleffects.co.uk)



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

*This document was created as a general guide for using Walleffects Ltd to complete projects and to help with specifications. This is a general overview and offers no guarantee for any problems that may arise. Walleffects Ltd or its employees will not be responsible or liable for any claim or action taken against them in relation to advice offered by this document.*