
Designed polished plaster Specification Details.

Description

These are lime based polished plaster finish that requires special skills and experienced applicators to achieve good high quality end results. Applications and products are provided directly from Walleffects ltd. This finish can vary depending on required result.

Site Name

[Add you site location here]

Areas to receive specialist finishes

[Add description here of all areas to be finished]

Drawings

[Add drawing reference number etc]

Substrate

[Add your preferred substrate here with a reference to the relevant data sheet.]

Render, drylined surfaces, plaster board are all suitable please check the substrate documents for more advice. Substrates all need to be fully dry, free from dust, dirt, moisture, straight, plumb and with no bumps or ridges.

Please check our **plaster substrate documents** for more details or email our technical adviser tech@walleffects.co.uk.

Finish

[Add your custom finish here. Send a copy of any required design to Walleffects prior to specification to check it is achievable.]

Options.

Imprinted logo or design

Raised logo or design.

Multi coloured polished finishes.

Block panels.

Other

Textures required for finish

Surface 1- [add your surface details here, ie polished Classic or Carrara Marmorino as per your sample.]

Surface 2 [add surface details here]

Surface 3 – [add surface details here]

Design Sizes

[ie add block sizes, fonts or logo sizes]

Colour

Colour no [add our number here for all textures]

Sample reference [add numbers here]

Custom colours [add a reference here, ie RAL or paint number]

Polished Plaster finishes are not a uniform colour and will have natural shade variations. Small samples may not show this.

Thickness

Various. This can be provided when design are finalised.

Programme

Application times will vary depending on the specific project. Finishes need to be applied late in the construction normally when decorating is taking place. Applications are normally booked 8 weeks in advance. Designed custom finishes done in polished plasters have a minimum 3 days application time due to the various required layers. Please contact Walleffects for specific application times.

This document was created as a general guide for using Walleffects Ltd to complete projects and to help with specifications. This is a general overview and offers no guarantee for any problems that may arise. Walleffects Ltd or its employees will not be responsible or liable for any claim or action taken against them in relation to advice offered by this document.