

Dilavato [washed stone] Product Data Sheet

Recommended Use:

Natural lime based wall stucco for decorative finishes on interior and exterior surfaces.

Ingredients

Finely filter hydrated and hydraulic lime

Grains of expensive coloured marble (special powdered marble granules sifted and selected according to granule size).

Water and acrylic binder (no more than 3% total in volume)

Physical characteristics:

Excellent decorative effect

Excellent drying capacity

Natural anti-mould and mildew

Coating capacity

Excellent filler properties

Excellent workability

Dry power material

Fire, Smoke & Explosive hazards

Non combustible material.

Toxicity including VOC:

0g VOC per litre

Skin absorption

May cause irritation to skin. Wash well with water and keep out of the reach of children. Seek medical attention if symptoms persist.

Eye absorption

Avoid contact with eyes at all times as it may cause irritation. Seek medical attention if eyes have been in contact with this product.

Inhalation:

Always use a good mask when mixing as this is a dusty powder material.

Ingestion

Not suitable for human consumption. Seek medical advice if consumed

Packaging

20kg plastic buckets and 25kg paper sacks.

Disposal

Product must be disposed of according to local regulations.
Containers must be recycled.

Storage

Keep in a dry store.

Mixing

Add water and mix in a small cement mixer or by drill in a container. Always wear a mask and gloves.

Coverage



Phone: +44(0) 28 81648902

Wall Effects Ltd
Unit 1
60 Slievebeg Road
Plumbridge
Omagh
Co.Tyrone
BT79 8LB

6/7 kg material per meter sq.

Drying Time

Touch dry - first coat: 3-6 hours at 20°C

Carbonation - 8-14 hours at 20°

Fully dry - 150 days

Application – Using trowels and washed with a sponge float.

Substrate – Lime based plaster fine or rough as desired.

Shelf Life - 1 year