
Flooring Marmorino Specification Details.

Description

This is a lime based polished floor finish that requires special skills and experienced application skills to achieve good high quality end results. Applications and products are provided directly from Walleffects Ltd. Flooring Marmorino has a matt shine on the surface which is smooth and cold to the touch. This product is only suited to low traffic areas in a domestic like settings.

Site Name

[Add you site location here]

Areas to receive specialist finishes

[Add description here of all areas to be finished]

Drawings

[Add drawing reference number etc]

Substrate

A fully dried concrete floor with a fine finish.

Email our technical adviser tech@walleffects.co.uk for more information

Finish

[Add you finish here]

As per sample

Colour

Colour no *[add number here]*

Sample reference *[add number here]*

Custom colours *[add a reference here, ie RAL or paint number]*

Polished Floor finishes are not a uniform colour and will have natural shade variations.

Small samples may not show this.

Thickness

2mm to 3mm



Phone: +44(0) 28 81648902

Wall Effects Ltd
Unit 1
60 Slievebeg Road
Plumbridge
Omagh
Co.Tyrone
BT79 8LB

Programme

Application times will vary depending on the specific project. Finishes need to be applied late in the construction normally when decorating is taking place. Applications are normally booked 8 weeks in advance. Flooring Marmorino has a minimum 3 days application time due to the various required layers. Please contact Walleffects for specific application times.

This document was created as a general guide for using Walleffects Ltd to complete projects and to help with specifications. This is a general overview and offers no guarantee for any problems that may arise. Walleffects Ltd or its employees will not be responsible or liable for any claim or action taken against them in relation to advice offered by this document.