

There are two main products used for creating this effect:

- Sand Stone Effects
- Aquaglass

### **Sand Stone Effects**

#### **Recommended Use:**

A textured decorative coating with can be left as a finish or used to create textures for our washes and waxes. Sand Stone Effects are perfect for cracking with our crackle solution creating more depth than traditional paint effects.

#### **Ingredients and CAS numbers**

Acrylic copolymer emulsion	Proprietary
Surfactant	Proprietary
Water	7732 – 18 -5
Coalescing agent	25265 – 77 – 4
Titanium dioxide	13463 – 67 – 7
Kaolin clay	1332 – 58 – 7
Calcium carbonate	471 – 34 – 1
Microspheres	66402 – 68 - 4
Mica	12001 – 26 – 2

#### **Physical characteristics:**

Thick paste  
No odour  
Resistant  
Multiple effects

---

## Fire, Smoke & Explosive hazards

Fire Growth Rate Index-04: Class O British and Class B Euroclass  
Smoke Growth Rate Index: Class O British and Class B Euroclass  
Non combustible material.

Tests carried out in accordance with BSEN 13823:2002

## Toxicity including VOC

50g per litre

## Skin absorption

No evidence of harmful effects. Avoid skin contact as a precaution. Seek medical advice if unusual symptoms occur.

## Eye absorption

If in contact with eyes it may cause irritation. In case of contact with eyes rinse thoroughly with water. Seek medical advice if unusual symptoms occur.

## Inhalation:

No evidence of harmful effects. Avoid inhalation as a precaution. Seek medical advice if unusual symptoms occur and move victim to the fresh air.

## Ingestion

Products are not suitable for human consumption. If victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomit, rinse mouth and administer more water. Seek medical attention.

## Packaging

500ml, 2.5L and 5L Plastic containers.

### **Disposal**

Product must be disposed of according to local regulations.  
Containers must be recycled.

### **Storage**

Protect from frost, storing upright in temperatures between 5 and 30 degrees C. Do not freeze.

### **Mixing**

Ready to use paste.

### **Coverage**

1-2. metres sq. per litre.

### **Drying Time**

20 minutes – 1 hour depending on film thickness.

**Application** – by various tools e.g. spatulas, sponges, and roller.

### **Substrate**

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

**Shelf Life** - 2 years in original packaging.

## **Aquaglass Crackle Solution**

### **Recommended Use:**

For cracking paints and plasters. Suitable for interior decorative finishes.

### **Ingredients and CAS numbers**

Acrylic copolymer emulsion	Proprietary
Surfactant	Proprietary
Water	7732 – 18 -5
Coalescing agent	25265 – 77 – 4

### **Physical characteristics:**

Liquid

### **Fire, Smoke & Explosive hazards**

Non-flammable

### **Toxicity including VOC**

10g per litre

### **Skin absorption**

No evidence of harmful effects from available information. If symptoms occur flush with running water and seek medical advice.

### **Eye absorption**

Avoid contact with eyes at all times as irritation may occur. If contact occurs, rinse eyes thoroughly with water. Seek medical attention if symptoms persist.

### **Inhalation:**

No evidence of harmful effects from available information. If symptoms occur move victim to fresh air.

### **Ingestion**

Products are not suitable for human consumption. If consumed and if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomit, rinse mouth and administer more water. Obtain medical attention.

### **Packaging**

500ml plastic containers.  
2.5L plastic containers.  
5L plastic containers.

### **Disposal**

Product must be disposed of according to local regulations.  
Containers must be recycled.

### **Storage**

Protect from frost, storing upright in temperatures between 5 and 30 degrees C.

### **Mixing**

Shake before use.

### **Coverage**

8 – 10 meters sq per litre



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

### **Drying Time**

1/2 hour at room temperature.

### **Application**

Roller or brush application in 2 coats. Needs to be touch dry between coats.

### **Substrate**

Any of the Walleffects paint range or matt and vinyl emulsion.

### **Shelf Life**

2 Years