

There are three different types of primer:

- Sharktooth Primer
- Fond Fine Primer
- Acrylic Primer

### **Sharktooth Primer**

#### **Recommended Use:**

Primer for decorative paint finishes on interior and exterior surfaces.

#### **Ingredients and CAS numbers**

Acrylic copolymer	Unknown
Emulsion	
Surfactant	Unknown
Water	7732 - 18 - 5
Coalescing Agents	57 - 55 - 6
Titanium Dioxide	13463-67-7
Calcium Carbonate	471-34-1

#### **Physical characteristics:**

Normal paint like primer  
Resistant  
No odour  
Can be tinted.

#### **Fire, Smoke & Explosive hazards**

Non flammable or combustible

---

**Toxicity including VOC:**

40g per litre

**Skin absorption**

No evidence of harmful effects from available information. If symptoms occur flush with running water and wash with soap and water. If symptoms persist seek medical attention.

**Eye absorption**

Avoid contact with eyes at all times as irritation may occur. If contact occurs, rinse eyes thoroughly with water. Seek medical attention if symptoms persist.

**Inhalation:**

No known risks. If symptoms occur move victim to fresh air and seek medical attention.

**Ingestion**

Products are not suitable for human consumption. If consumed and if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in vomits, rinse mouth and administer more water. Obtain medical attention.

**Packaging**

Metal tins and Plastic containers.

**Disposal**

Product must be disposed of according to local regulations.  
Containers must be recycled.

**Storage**

Protect from frost, storing upright in temperatures between 5 and 30 degrees C.



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

### **Mixing**

Stir well before use. Tint with universal colorants to a maximum of 5% by volume.

### **Coverage**

6 to 10 meter sq per litre.

### **Application**

Roller or brush applications.

### **Substrate**

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

### **Shelf Life**

2 years

## **Fond Fine Primer**

### **Recommended Use:**

Primer for Marmorino Veneziano, Lime Paint, Intonachino, cement and all lime based products.

### **Ingredients /CAS numbers**

99638-59-2  
7732-18-5  
471-34-1  
14807-96-6  
1318-59-8  
16389-88-1  
14808-60-7  
9004-65-3  
107-41-5  
138-31-4  
1310-73-2

### **Physical characteristics:**

Opaque  
Slightly rough

### **Fire, Smoke & Explosive hazards**

Non-flammable.

### **Toxicity including VOC:**

0gl of voc per litre.

### **Skin absorption**

In case of contact with eyes or skin, rinse thoroughly with water. Keep out of reach of children.

### **Eye absorption**

Avoid contact with eyes at all times as it may cause irritation. In case of contact with eyes, rinse thoroughly with water. Seek medical attention if eyes have been in contact with this product.

### **Inhalation:**

A wet material with little odour. Remove victim to fresh air if any unusual symptoms occur.

### **Ingestion**

Products are not suitable for human consumption. Seek medical advice if consumed.

### **Packaging**

14lt plastic containers

5lt plastic containers

### **Disposal**

Product must be disposed of according to local regulations.

Containers must be recycled.

### **Storage**

Product maintains its characteristics best if protected from extreme heat or cold. Keep away from children.



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

### **Mixing**

Add 30% to 40% water and mix well.

### **Coverage**

5.5 meter sq per litre. {Diluted}

### **Drying Time**

Touch dry - 2 hours at 20°C

Below the surface - 24 hours at 20°C

**Application** - by hand with brush or roller.

**Substrate** – suitable for most substrates.

**Shelf Life** - 1 year

---

## **Acrylic Primer**

### **Recommended Use:**

Primer Normal is used in four situations. These are:

1. When the substrate is dusty.
2. To strengthen a fragile surface this has, for example, old paint or lime paint which is adherent, yet soft.
3. On plaster to separate a slightly acidic material such as gypsum from an alkaline material such as lime.
4. To help the wall absorb uniformly when it has more than one substrate.

### **Ingredients and CAS numbers**

Pure acrylic resin suitable for all alkaline materials.

### **Physical characteristics:**

Thick Liquid.

### **Fire, Smoke & Explosive hazards**

Non combustible material.

### **Toxicity including VOC:**

0gl of voc per litre

### **Skin absorption**

None know but advise wearing gloves. In case of contact with skin rinse thoroughly with water.

### **Eye absorption**

Avoid contact with eyes at all times. In case of contact with eyes, rinse thoroughly with water.

### **Inhalation:**

Remove victim to fresh air if any unusual symptoms occur.

### **Ingestion**

Products are not suitable for human consumption. Seek medical advice if consumed.

### **Packaging**

1lt. containers

10 lt. Containers

### **Disposal**

Product must be disposed of according to local regulations. Containers must be recycled.

### **Storage**

Protect from frost storing at temperatures between 5 and 30 degrees C.

### **Mixing**

Dilute it with 1 part primer and 7 or 8 parts water and mix well and apply as usual with a roller or paint brush.

Use plentifully, to penetrate and reinforce old paint or plaster which is flaky and a more concentrated solution (1:7) on dry wall, wood, or cement.



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

### **Coverage**

1 litre per 28/34 meter sq.

### **Drying Time**

2 hours at 20°C to the touch

24 hours at 20°C below the surface

**Application** – Apply to area using a paint brush or roller.

**Substrate** – Plasterboard, plaster, wood, metal or plasterboard.

### **Shelf Life**

1year