

Aquaglass

Recommended Use:

For cracking paints and plasters. Suitable for interior decorative finishes.

Ingredients and CAS numbers

| | |
|----------------------------|----------------|
| Acrylic copolymer emulsion | Proprietary |
| Surfactant | Proprietary |
| Water | 7732 – 18 -5 |
| Coalescing agent | 25265 – 77 – 4 |

Physical characteristics:

Liquid

Fire, Smoke & Explosive hazards

Non-flammable

Toxicity including VOC

10g per litre

Skin absorption

No evidence of harmful effects from available information. If symptoms occur flush with running water and seek medical advice.

Eye absorption

Avoid contact with eyes at all times as irritation may occur. If contact occurs, rinse eyes thoroughly with water. Seek medical attention if symptoms persist.

Inhalation:

No evidence of harmful effects from available information. If symptoms occur move victim to fresh air.

Ingestion

Products are not suitable for human consumption. If consumed and if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomit, rinse mouth and administer more water. Obtain medical attention.

Packaging

500ml plastic containers.

2.5L plastic containers.

5L plastic containers.

Disposal

Product must be disposed of according to local regulations.

Containers must be recycled.

Storage

Protect from frost, storing upright in temperatures between 5 and 30 degrees C.

Mixing

Shake before use.

Coverage

8 – 10 meters sq per litre



Phone: +44(0) 28 81648902

Wall Effects Ltd
Unit 1
60 Slievebeg Road
Plumbridge
Omagh
Co.Tyrone
BT79 8LB

Drying Time

1/2 hour at room temperature.

Application

Roller or brush application in 2 coats. Needs to be touch dry between coats.

Substrate

Any of the Walleffects paint range or matt and vinyl emulsion.

Shelf Life

2 Years