

Base Effects

Recommended Use:

For adding texture to any decorative finish on interior surfaces. Can be used as a finish without extra coatings if required. Suitable for decoration of domestic or commercial buildings.

Ingredients and CAS numbers

| | |
|----------------------------|----------------|
| Acrylic copolymer emulsion | Proprietary |
| Surfactant | Proprietary |
| Water | 7732 – 18 -5 |
| Coalescing agent | 25265 – 77 – 4 |
| Titanium dioxide | 13463 – 67 - 7 |
| Kaolin clay | 1332 – 58 - 7 |
| Calcium carbonate | 471 – 34 – 1 |

Physical characteristics:

Water Based.

Thick paste

Washable

Sheen – satin or flat

Can be coloured, please select from our colour chart or request a custom colour.

No smell of solvent

Suitable for creating multiple effects

Fire, Smoke & Explosive hazards

Fire Growth Rate Index-04: Class O British and Class B Euroclass

Smoke Growth Rate Index: Class O British and Class B Euroclass

Non combustible material.

Tests carried out in accordance with BSEN 13823:2002

Voc

60g voc per litre.

Colour

White, Red, Black and neutral for tinting

Skin absorption

No evidence of harmful effects from available information. If symptoms occur flush with running water and wash with soap and water. If symptoms persist seek medical attention.

Eye absorption

Avoid contact with eyes at all times as irritation may occur. If contact occurs, rinse eyes thoroughly with water. Seek medical attention if symptoms persist.

Inhalation:

If symptoms occur move victim to fresh air.

Ingestion

Products are not suitable for human consumption. If consumed and if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in vomits, rinse mouth and administer more water. Obtain medical attention.

Packaging

500ml, 2.5L and 5L Plastic containers

Disposal

Product must be disposed of according to local regulations.
Containers must be recycled.

Storage

Protect from frost, storing upright in temperatures between 5 and 30 degrees C. Do not freeze.

Mixing

Mix with a drill attachment.



Phone: +44(0) 28 81648902

Wall Effects Ltd
Unit 1
60 Slievebeg Road
Plumbridge
Omagh
Co.Tyrone
BT79 8LB

Coverage

2.5 - 5 meters sq. per litre.

Drying Time

1 hour or longer depending on film thickness

Application

Various tools e.g. rollers, trowels, spatulas, sponges or any specialist decorator's tool.

Substrate

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

Shelf Life

2 years in original packaging.