
Extender

Recommended Use:

Interior use, new and existing. For decorative finishes on shops, homes, offices.

Ingredients and CAS numbers

Acrylic copolymer emulsion	Unknown
Surfactant	Unknown
Water	7732 - 18 - 5
Coalescing agents	57 - 55 - 6
Mica	66402 – 68 – 4

Physical characteristics:

Thick gel
Washable (in some applications)
No odour
Multiple effects
Can be coloured

Fire, Smoke & Explosive hazards

Non-flammable.

Toxicity including VOC:

500g voc per L

Skin absorption

No evidence of harmful effects from available information. Flush skin with water.

Eye absorption

Avoid contact with eyes at all times. May cause irritation. Rinse eyes thoroughly with water. Seek medical attention if irritation persists.

Inhalation:

Move victim to fresh air if any unusual symptoms occur.

Ingestion

Products are not suitable for human consumption. In case of consumption, if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomits, rinse mouth and administer more water. Obtain medical attention.

Packaging

500ml sample plastic containers

2.5L plastic containers

5L plastic containers

Disposal

Product must be disposed of according to local regulations.

Containers must be recycled.

Storage

Protect from frost storing upright in temperatures between 5 and 30 degrees C. Do not freeze.

Mixing

Shake before use.

Coverage

7 – 10 meters sq. per litre.

Drying Time

1 hour or longer depending on film thickness.

Application

By variable tools e.g. sponges, spatula.

Substrate

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

Shelf Life - 2 years in original packaging.