

---

## **Metallic Paint**

### **Recommended Use:**

For decorative finishes in domestic and commercial buildings.

### **Ingredients and CAS numbers**

Acrylic emulsion	Unknown
Aluminum flake	7429 – 90 - 5
Copper	7440 – 50 – 8
Zinc	7440 – 66 - 6
Water	7440 – 66 - 6
Coalescing agents	57 - 55 – 6
Mica	66402 – 68 – 4

### **Physical characteristics:**

White liquid  
No odour  
Resistant  
Multiple effects

### **Fire, Smoke & Explosive hazards**

Non-flammable

### **Toxicity including VOC:**

50g voc per litre.

### **Skin absorption**

No evidence of harmful effects from available information

---

### **Eye absorption**

May cause irritation if in contact with eyes. Wash thoroughly with water. Seek medical advice.

### **Inhalation:**

May cause irritation of stomach with abdominal discomfort.

### **Ingestion**

Products are not suitable for human consumption. Give 2 glasses of water and induce vomiting, if victim is alert. Seek medical advice if consumed.

### **Packaging**

500ml and 2.5L plastic containers.

### **Colours**

Gold and silver base for tinting

### **Disposal**

Product must be disposed of according to local regulations.  
Containers must be recycled.

### **Storage**

Protect from frost, storing upright in temperatures between 5 and 30 degrees C.

### **Mixing**

Ready to tint and pre-tinted containers available.

### **Coverage**

3.5 metres sq. per L.



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

### **Drying Time**

20 minutes – 1 hour

Fully dry – 24 hours

### **Application**

Brush, roller, spray.

### **Substrate**

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

**Shelf Life** - 1 year in original packaging.