
Metallic Wax

Recommended Use: For decoration and protection of our Base Effects. Interior use only. Suitable for decoration of all domestic or commercial buildings.

Ingredients and CAS numbers

| | |
|----------------------------|---------------|
| Acrylic copolymer emulsion | Unknown |
| Surfactant | Unknown |
| Water | 7732 - 18 – 5 |
| Coalescing agents | 57 - 55 – 6 |

Physical characteristics:

Flowing paste
Metallic
Washable (in some applications)
Multiple effects available
Resistant
No smell of solvent
Suitable for colouring
Can be painted over if required

Fire, Smoke & Explosive hazards

Fire Growth Rate Index-04: Class O British and Class B Euroclass
Smoke Growth Rate Index: Class O British and Class B Euroclass
Non combustible material.

Tests carried out in accordance with BSEN 13823:2002

Toxicity including VOC:

70g voc per litre

Skin absorption

No evidence of harmful effects from available information. If symptoms occur flush with running water and wash with soap and water. If symptoms persist seek medical attention.

Eye absorption

Avoid contact with eyes at all times as irritation may occur. If contact occurs, rinse eyes thoroughly with water. Seek medical attention if symptoms persist.

Inhalation:

If symptoms occur move victim to fresh air.

Ingestion

Products are not suitable for human consumption. If consumed and if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in vomits, rinse mouth and administer more water. Obtain medical attention.

Packaging

Plastic containers

Disposal

Products must be disposed of according to local regulations.
Containers must be recycled.

Storage

Protect from frost, storing upright in temperatures between 5 and 30 degrees C.

Mixing

Ready to use



Phone: +44(0) 28 81648902

Wall Effects Ltd
Unit 1
60 Slievebeg Road
Plumbridge
Omagh
Co.Tyrone
BT79 8LB

Coverage

10 metres sq per litre.

Drying Time

20 minutes – 1 hour depending on film thickness

Application – by various tools e.g. spatulas, sponges.

Substrate

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

Shelf Life - 2 years in original packaging.