

Sand Stone Effects

Recommended Use:

A textured decorative coating with can be left as a finish or used to create textures for our washes and waxes. Sand Stone Effects are perfect for cracking with our crackle solution creating more depth than traditional paint effects.

Ingredients and CAS numbers

Acrylic copolymer emulsion	Proprietary
Surfactant	Proprietary
Water	7732 – 18 -5
Coalescing agent	25265 – 77 – 4
Titanium dioxide	13463 – 67 – 7
Kaolin clay	1332 – 58 – 7
Calcium carbonate	471 – 34 – 1
Microspheres	66402 – 68 - 4
Mica	12001 – 26 – 2

Physical characteristics:

Thick paste
No odour
Resistant
Multiple effects

Fire, Smoke & Explosive hazards

Fire Growth Rate Index-04: Class O British and Class B Euroclass
Smoke Growth Rate Index: Class O British and Class B Euroclass
Non combustible material.

Tests carried out in accordance with BSEN 13823:2002

Voc

60g voc per litre

Colour

White – can be tinted.

Skin absorption

No evidence of harmful effects. Avoid skin contact as a precaution. Seek medical advice if unusual symptoms occur.

Eye absorption

If in contact with eyes it may cause irritation. In case of contact with eyes rinse thoroughly with water. Seek medical advice if unusual symptoms occur.

Inhalation:

No evidence of harmful effects. Avoid inhalation as a precaution. Seek medical advice if unusual symptoms occur and move victim to the fresh air.

Ingestion

Products are not suitable for human consumption. If victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomit, rinse mouth and administer more water. Seek medical attention.

Packaging

500ml, 2.5L and 5L Plastic containers.

Disposal

Product must be disposed of according to local regulations.
Containers must be recycled.

Storage

Protect from frost, storing upright in temperatures between 5 and 30 degrees C. Do not freeze.

Mixing

Ready to use paste.

Coverage

1-2. meters sq. per litre.

Drying Time

20 minutes – 1 hour depending on film thickness.

Application – by various tools e.g. spatulas, sponges, and roller.

Substrate

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

Shelf Life - 2 years in original packaging.