

---

## **Tadelakt Product Data Sheet**

### **Recommended Use:**

Natural lime based wall stucco for decorative finish on interior and exterior surfaces.

### **Ingredients**

Finely filter hydrated and hydraulic lime  
Grains of stone  
Water and acrylic binder

### **Physical characteristics:**

Excellent decorative effect  
Excellent drying capacity  
Natural anti-mould and mildew  
Coating capacity  
Excellent filler properties  
Excellent workability  
Dry power material

### **Fire, Smoke & Explosive hazards**

Non combustible material.

### **Toxicity including VOC:**

0g VOC per litre

### **Skin absorption**

May cause irritation to skin. Wash well with water and keep out of the reach of children. Seek medical attention if symptoms persist.

### **Eye absorption**

Avoid contact with eyes at all times as it may cause irritation. Seek medical attention if eyes have been in contact with this product.

### **Inhalation:**

Always use a good mask when mixing as this is a dusty powder material.

### **Ingestion**

Not suitable for human consumption. Seek medical advice if consumed

### **Packaging**

20kg plastic buckets

### **Disposal**

Product must be disposed of according to local regulations.  
Containers must be recycled.

### **Storage**

Keep in a dry store.

### **Mixing**

Add water and mix in a small cement mixer or by drill in a container. Always wear a mask and gloves.

### **Coverage**

2.2 – 2.5 kg material per meter sq.

### **Drying Time**



Phone: +44(0) 28 81648902

Wall Effects Ltd  
Unit 1  
60 Slievebeg Road  
Plumbridge  
Omagh  
Co.Tyrone  
BT79 8LB

---

Touch dry - first coat: 3 hours at 20°C  
Carbonation - 48 hours at 20°  
Fully dry - 180 days

**Application** – Metal and plastic trowels.

**Substrate** – Lime based plaster fine or rough as desired.

**Shelf Life** - 1 year